

## TECHNICAL DESCRIPTION



<b>TYPE:</b>	safety sandal for professional use designated as S1
<b>PRODUCT NAME:</b>	Z91002 (S1) BENNON SANDÁL LUX
<b>SIZE RUN:</b>	36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50
<b>STANDARD:</b>	EN ISO 20345:2004/A1:2007
<b>REQUIRED:</b>	EN ISO 20345 S1

### Material characteristics:

<b>Upper leather:</b>	cow nubuck, thickness 1,8-2,0mm
<b>Collar, tongue:</b>	cow nubuck, thickness 1,8-2,0mm
<b>Sock lining:</b>	antistatic, non-woven construction, thickness 2,0mm
<b>Lining:</b>	<ul style="list-style-type: none"><li>- vamp: non woven material</li><li>- back quarters: textile material MESH, orange colour</li></ul>
<b>Collar padding:</b>	polyurethan foam, thickness 15mm
<b>Insert counter:</b>	thermoplastic, thickness 1,8-2,0mm
<b>Insert insock:</b>	anatomic,exchangable, material mesh-eva, orange colour
<b>Heel grip:</b>	microfiber, colour gray
<b>Sewing:</b>	orange colour , PES
<b>Toe cap:</b>	steel 522, impact resistance min 200J
<b>Midsole:</b>	polyuretan, colour gray

# BENNON

EXPERIENCE OF EXPERTS

<b>Outsole:</b>	T017, polyurethane, colour black, oil and fuel resistance
<b>Product description:</b>	light, flexible, universal use, also for internal conditions, light outsole's colour against the „writting“ at floor
<b>Purpose:</b>	Safety shoes for professional use which is intended for a broad group pf workers of various professions. Steel toe cap protects toes against injuries.
<b>Labelling:</b>	In accordance with the appropriate standard.
<b>Packaging:</b>	10 pairs in one carton  36-43# 0,60*0,38*0,34 m 44-48# 0,62*0,425*0,365 m
<b>Weight:</b>	1052 gr / pair (size 42)

## FOOTWEAR DESIGNATION

BENNON  
SANDAL LUX  
Z91002(S1) / SA-364B  
SIZE: 42  
DATE: .... / 2014  
CE EN ISO 20345:2011 S1 SRC

Zlín 30.1.2014